AUTHOR INDEX

Bauchau, O.A., p. 170
Belchamber, R.M., p. 420
Bert, C.W., p. 282
Betteridge, D., p. 420
Bigelow, C.A., p. 549
Carlsson, L., p. 238
Chang, D.C., p. 182
Chi, Z., p. 196
Chim, E.S.M., p. 114, 250, 299
Choo, V.K.S., p. 344
Chou, T., p. 26, 92, 196, 399
Chow, Y.T., p. 420
Crochet, M.J., p. 316
Cudby, M.E.A., p. 420
Du, S., p. 511
Dumir, P.C., p. 478
Farley, G.L., p. 267
Fritz, P.J., p. 224
Ghandi, M.L., p. 478
Givler, R.C., p. 330
Goetz, T.P., p. 299
Gordaninejad, F., p. 282
Griffin, Jr., O.H., p. 449, 539
Gukasjan, L.E., p. 527
Gunnink, J.W., p. 508
Hamaguchi, Y., p. 64
Hawkes, A.G., p. 420
Hoenig, A., p. 231
Hull, D., p. 344
Ishikawa, T., p. 92, 399
Kaye, K.S., p. 368
Khetan, R.P., p. 182
Kolek, R.L., p. 368
Konishi, D.Y., p. 384
Lakkad, S.C., p. 2
Libove, C., p. 45
Lo, K.H., p. 384
Loos, A.C., p. 135
Lakshminarayana, H.V., p. 357
Manders, P.W., p. 26
Mansfield, E.H., p. 414
Morimoto, K., p. 464
Naerheim, Y., p. 105
Nath, Y., p. 478
Omoike, G., p. 316
Pipes, R.B., p. 330
Queeney, R.A., p. 224
Raghava, R.S., p. 368
Raju, I.S., p. 492
Ramana Murthy, P.V., p. 435
Rao, K.P., p. 435
Richards-Frandsen, R., p. 105
Roberts, J.C., p. 539
Rokhlin, S.I., p. 15
Shorshorov, M. Kh., p. 527
Shimokawa, T., p. 64
Springer, G.S., p. 135
Suzuki, T., p. 464
Thorat, H.T., p. 2
Ting, T.C.T., p. 49
Tolf, G., p. 77
Ustinov, L.M., p. 527
Vilmann, C.R., p. 316
Wang, S.S., p. 114, 210, 250, 299
Whitcomb, J.D., p. 492
Wood, D.G.M., p. 420
Wu, E.M., p. 384
Yang, J.N., p. 511
Yosomiya, R., p. 464
Yu, T.P., p. 299
Zahlan, N.M., p. 250
Zwiers, R.I., p. 49

SUBJECT INDEX

Acoustic emissions, from PP/glass fiber composites, p. 420
Adhesives, ultrasonic curing, p. 15
Aluminum/boron composites, p. 527
Automotive, p. 182
Biaxial compression, p. 45
Bilaminates, p. 45
Bimodular beams, p. 435
Bimodular materials, p. 282
Boron/epoxy laminates, p. 449
Buckle pattern, p. 45
Buffer strips, p. 549
Carbon-carbon, p. 435
Carbon 8-harness-satin laminate, p. 64

AUTHOR INDEX

Bauchau, O.A., p. 170
Belchamber, R.M., p. 420
Bert, C.W., p. 282
Betteridge, D., p. 420
Bigelow, C.A., p. 549
Carlsson, L., p. 238
Chang, D.C., p. 182
Chi, Z., p. 196
Chim, E.S.M., p. 114, 250, 299
Choo, V.K.S., p. 344
Chou, T., p. 26, 92, 196, 399
Chow, Y.T., p. 420
Crochet, M.J., p. 316
Cudby, M.E.A., p. 420
Du, S., p. 511
Dumir, P.C., p. 478
Farley, G.L., p. 267
Fritz, P.J., p. 224
Ghandi, M.L., p. 478
Givler, R.C., p. 330
Goetz, T.P., p. 299
Gordaninejad, F., p. 282
Griffin, Jr., O.H., p. 449, 539
Gukasjan, L.E., p. 527
Gunnink, J.W., p. 508
Hamaguchi, Y., p. 64
Hawkes, A.G., p. 420
Hoenig, A., p. 231
Hull, D., p. 344
Ishikawa, T., p. 92, 399
Kaye, K.S., p. 368
Khetan, R.P., p. 182
Kolek, R.L., p. 368
Konishi, D.Y., p. 384
Lakkad, S.C., p. 2
Libove, C., p. 45
Lo, K.H., p. 384
Loos, A.C., p. 135
Lakshminarayana, H.V., p. 357
Manders, P.W., p. 26
Mansfield, E.H., p. 414
Morimoto, K., p. 464
Naerheim, Y., p. 105
Nath, Y., p. 478
Omoike, G., p. 316
Pipes, R.B., p. 330
Queeney, R.A., p. 224
Raghava, R.S., p. 368
Raju, I.S., p. 492
Ramana Murthy, P.V., p. 435
Rao, K.P., p. 435
Richards-Frandsen, R., p. 105
Roberts, J.C., p. 539
Rokhlin, S.I., p. 15
Shorshorov, M. Kh., p. 527
Shimokawa, T., p. 64
Springer, G.S., p. 135
Suzuki, T., p. 464
Thorat, H.T., p. 2
Ting, T.C.T., p. 49
Tolf, G., p. 77
Ustinov, L.M., p. 527
Vilmann, C.R., p. 316
Wang, S.S., p. 114, 210, 250, 299
Whitcomb, J.D., p. 492
Wood, D.G.M., p. 420
Wu, E.M., p. 384
Yang, J.N., p. 511
Yosomiya, R., p. 464
Yu, T.P., p. 299
Zahlan, N.M., p. 250
Zwiers, R.I., p. 49

SUBJECT INDEX

Acoustic emissions, from PP/glass fiber composites, p. 420
Adhesives, ultrasonic curing, p. 15
Aluminum/boron composites, p. 527
Automotive, p. 182
Biaxial compression, p. 45
Bilaminates, p. 45
Bimodular beams, p. 435
Bimodular materials, p. 282
Boron/epoxy laminates, p. 449
Buckle pattern, p. 45
Buffer strips, p. 549
Carbon-carbon, p. 435
Carbon 8-harness-satin laminate, p. 64

Composite bonded joint, p. 511
Composite laminates, p. 210, p. 492, p. 511, p. 539
Constitutive models, p. 449
Contact-edge, p. 49
Cracked bodies, p. 231
Curing, p. 135
Curing stress, p. 449
Curved beams, p. 435
Cyclic degradation of properties, p. 114
Cyclic fatigue crack growth, p. 250
Cyclic fatigue loading, p. 250
Cylindrical bending, p. 282
Damage accumulation law, p. 114
Defects, p. 105
Delamination, p. 105, p. 210, p. 238
Design, p. 170, p. 511
Dilute suspension, p. 330
Dynamics, p. 77
Dynamic stress concentrations, p. 26
Edge notch, p. 357
Elastic stability, p. 45
Elevated temperature, p. 549
Energy absorption, of composites, p. 267
Fabric composites, p. 92
Failure criteria, p. 344
Failure location, p. 539
Failure mode, p. 539
Failure sequence, p. 26
Failure strength, p. 384
Fatigue, p. 105, p. 511
Fatigue crack propogation law, p. 250
Fatigue damage accumulation, p. 64
Fatigue fracture, p. 114
Fatigue life distribution, p. 64
Fatigue strength distribution, p. 64
Fiber composites, p. 77
Fiber orientation, p. 330
Fiber reinforced strip, p. 414
Fiber reinforcement, p. 26
Finite element analysis, p. 330, p. 357, p. 435, p. 449, p. 492, p. 539
Flexural properties, p. 464
Fracture, p. 231
Fracture mechanics, p. 210
Fracture mechanics analyses, p. 299
Fracture toughness, p. 2, p. 226
Fracture toughness testing of notched composites, p. 299
Free corner effect, p. 539
Fracture, p. 316
Fracture mechanics, p. 250
Fracture morphology, p. 105
Free-edge stresses, p. 492
Glass fiber, p. 344
Graphite epoxy, p. 92, p. 238, p. 539
Graphite/epoxy composite, p. 105, p. 368
Graphite/polyimide, p. 549
Homogeneous fatigue damage, p. 114
Hoop wound tubes, p. 344
Hybrids, p. 2
Impact, p. 182
Interface strength, p. 527
Interlaminar cracking, p. 210
Interlaminar stresses, p. 449, p. 492
Laminated beams, p. 435
Laminate elasticity solution, p. 210
Laminates, p. 282, p. 357
Layered composites, p. 49
Local composite stresses, p. 224
Loose carbon strands, p. 196
Load transfer, p. 414
Manufacturing composites, p. 135
Mechanical models, p. 92
Mechanical properties, p. 368
Microcrack initiation and growth, p. 114
Micropolar model
Mixed-mode fracture criteria, p. 299
Mixed-mode stress intensity factors, p. 210
Multi-axial testing, p. 344
Nondestructive tests, p. 182
Nonlinear static and transient analysis, p. 478
Notched composite laminates, p. 384
Notched composite specimen, p. 64, p. 250
Notch-tip stress intensities, p. 299
Numerical method, p. 330
Opening mode fracture toughness (K_{IQ}) p. 299
Optimizations, p. 170
Orthotropic plates, p. 45
Panels, SMC, p. 182
Particle reinforcement, p. 224
Photo-degradation, p. 464
Plain weave, p. 92
Polyester resins, p. 344
Polypropylene glass fiber composites, p. 420

Polyurethane foams, p. 464
Pre-stress, p. 26
PSN relations, p. 64
Random short fiber composite, p. 114
Random short-fiber SMC composite, p. 250, p. 299
Random short-fiber SMC composites, p. 299
Rectangular plates, p. 45
Residual stresses, p. 224
Reinforcement, p. 464
Rivet joints, p. 49
Rotating shafts, p. 170
Satin weave, p. 92
S-Glass, p. 549
Shear deformation, p. 282
Shear stress, p. 282
Shearing-mode fracture toughness (K_{IIQ}) p. 299
Short term high temperature exposure, p. 368
Simply supported plates, p. 45
Singularities, p. 49
SMC, p. 114
SMC Panels, p. 182
SMC, surface damage to panels, p. 182
Solid/hollow section beams, p. 435
Specially orthotropic laminates, p. 508
Spectrum loading, p. 511
Static bending, p. 282
Strain energy release rates, p. 210
Strength distribution, p. 26
Strength, effect of loose carbon strands, p. 196
Strength enhancement, p. 26
Stress analysis, p. 492
Stress concentration, p. 414
Stress distribution/concentration, p. 357
Stress intensity factor range, p. 250
Structural adhesive curing, p. 15
Temperature-dependent properties, p. 449
Thermal deformation, p. 92
Thermal degradation, p. 464
Thermal stresses, p. 449, p. 539
Thick section, welding, p. 368
Thin circular plates, p. 478
Transverse shear correction coefficient, p. 282
Ultrasonic curing, adhesives, p. 15
Vibrations, p. 170
Weight loss during exposure, p. 368
Woven fabric composites, p. 399